

H1) PRESSURE SAFETY SYSTEMS



Art. 241

Female membrane safety valve. PN 10, max. working temperature 110°C, opening overpressure 20%, closing pressure 20%.

The product complies the Ped. 97/23/CE norm - categoria IV D.M. 1.12.75, D.Lgs. 25.02.2000. CE n. 0425 approval.

ART.	SIZE	ATM.	CODE	PACKAGING		
241	1/2	1,5	91241ADAC	1	50	
241	1/2	1,8	91241ADBC	1	50	
241	1/2	2	91241ADAD	1	50	
241	1/2	2,5	91241ADAE	1	50	
241	1/2	3	91241ADAF	1	50	
241	1/2	3,5	91241ADAG	1	50	
241	1/2	4	91241ADAH	1	50	
241	1/2	5	91241ADAL	1	50	
241	1/2	6	91241ADAN	1	50	
241	1/2	7	91241ADAP	1	50	
241	1/2	8	91241ADAQ	1	50	
241	1/2	9	91241ADAR	1	50	
241	1/2	10	91241ADAS	1	50	
241	3/4	1,5	91241AEAC	1	50	
241	3/4	1,8	91241AEBC	1	50	
241	3/4	2	91241AEAD	1	50	
241	3/4	2,5	91241AEAE	1	50	
241	3/4	3	91241AEAF	1	50	
241	3/4	3,5	91241AEAG	1	50	
241	3/4	4	91241AEAH	1	50	
241	3/4	5	91241AEAL	1	50	
241	3/4	6	91241AEAN	1	50	
241	3/4	7	91241AEAP	1	50	
241	3/4	8	91241AEAQ	1	50	
241	3/4	9	91241AEAR	1	50	
241	3/4	10	91241AEAS	1	50	
241	1"	1,5	91241AFAC	1	50	
241	1"	1,8	91241AFBC	1	50	
241	1"	2	91241AFAD	1	50	
241	1"	2,5	91241AFAE	1	50	
241	1"	3	91241AFAF	1	50	
241	1"	3,5	91241AFAG	1	50	
241	1"	4	91241FAFH	1	50	
241	1"	5	91241AFAL	1	50	
241	1"	6	91241AFAN	1	50	
241	1"	7	91241AFAP	1	50	
241	1"	8	91241AFAQ	1	50	
241	1"	9	91241AFAR	1	50	
241	1"	10	91241AFAS	1	50	