

BRASS SOLENOID VALVE FOR GAS WITH MANUAL NA



Product Description

Gas Solenoid Normally open brass cut-out without tension - M16/230 Vac

NOTE: Other voltages on request

Version with max pressure 6 bar 230 Vac

 0497 solo only **6 bar**

PRESSIONE MAX 500 Mb
P. MAX 500 Mb

Properties

Impiego	Gas non aggressivi delle 3 famiglie (gas secchi)
Temperatura di esercizio	-15°/+60°C
Tensione	12 V, 24 V, 110 V, 230 V
Potenza assorbita	7 VA (8 VA Ø 1")
Grado di protezione /	IP 65

Variants

Code	Mod. ø	Conf./Pack
50331	Ø 1/2" FF. ottone - assorb. 7 VA	10
50331 A	Ø 3/4" FF. ottone - assorb. 7 VA	10
50331 B	Ø 1" FF. ottone - assorb. 8 VA	5
50331/6	Ø 1/2" FF. ottone - assorb. 7 VA (max 6 bar)	10
50331 A/6	Ø 3/4" FF. ottone - assorb. 7 VA (max 6 bar)	10
50331 B/6	Ø 1" FF. ottone - assorb. 8 VA (max 6 bar)	5

To view or download the price list click [Catalogs](#)
For further information on the product please contact our [technical department](#)

<http://www.tecnogas.net/en/products/elettrovalvola-per-gas-in-ottone-a-riarmo-manuale-na>