

## rpm measuring instrument

**testo 460 – Pocket-sized  
non-contact rpm measurement**

---

Optical rpm measurement with LED measurement spot marking

---

Min./max. values

---

Display illumination

---

Protective cap for safe storage

---

Incl. wrist strap and belt holder

---



Illustration 1/1

The especially handy, pocket-sized rpm measuring instrument testo 460 optically measures rpm, e.g. on ventilators and shafts. The ideal distance to the measurement object is between 10 and 40 cm. Simply attach a reflective marker (optional) to the measurement object, point the visible measurement spot at the reflective marker, and measure. Min./max. values are directly displayed at the press of a button.

The Hold-button allows particularly convenient reading of the measurement values. The illuminated display enables easy read-out of the measurement values even in bad lighting. testo 460 is very small, handy and easy to operate. The clip-on protective cap, wrist strap and a belt holder provide safe storage, ensuring an especially long working life.

## Technical data / Accessories

### testo 460

testo 460 measuring instrument for rpm  
incl. protection cap, batteries, belt holder  
and calibration protocol

Part no. 0560 0460



#### Sensor type **optical**

Measuring range	100 to 29999 rpm
Accuracy ±1 digit	±(0.02 % of m.v.)
Resolution	0.1 rpm (100 to 999.9 rpm) 1 rpm (1000 to 29999 rpm)

#### General technical data

Selectable units	rpm, rps
Measuring rate	0.5 s
Storage temperature	-40 to +70 °C
Operating temperature	0 to +50 °C
Battery type	2 AAA micro batteries
Battery life	20 h (average, without display illumination)
Weight	85 g (incl. battery and protective cap)
Dimensions	119 x 46 x 25 mm (incl. protective cap)
Protection class	IP40

#### Accessories for measuring instrument

#### Part no.

Reflectors, self-adhesive (1 pack = 5 off, each 150 mm long)	0554 0493	
Belt holder	0516 4007	
ISO calibration certificate/rpm, Calibration points freely selectable from 10 to 99500 rpm	0520 0114	