

# FOR ALUMINUM GAS SOLENOID VALVE WITH MANUAL RESET NA



## Product Description

Solenoid Valve for Gas aluminum Normally open tension-free manual reset - 230 Vac  
• Version Threaded FF

**NOTE: Other voltages on request**

**VERSION AVAILABLE WITH P. MAX 6 bar**  
*INCREASE OF 25% FROM NORMAL PRICE*

 **0497** solo **6 bar**

**PRESSIONE MAX 500 Mb**  
P. MAX 500 Mb

## Properties

Impiego	Gas non aggressivi delle 3 famiglie (gas secchi)
Temperatura di esercizio	-15°/+60°C
Tensione	12 V, 24 V, 110 V, 230 V
Potenza assorbita	20-23 VA
Grado di protezione /	IP 65

## Variants

Code	Mod. ø	Conf./Pack
50332	Ø 3/4" FF. alluminio	10
50333	Ø 1" FF. alluminio	5
50334	Ø 1 1/4" FF. alluminio	5
50335	Ø 1 1/2" FF. alluminio	5
50336	Ø 2" FF. alluminio	5

To view or download the price list click [Catalogs](#)  
For further information on the product please contact our [technical department](#)

<http://www.tecnogas.net/en/products/elettrovalvola-per-gas-in-alluminio-a-riarmo-manuale-na-3>