

# FOR ALUMINUM GAS SOLENOID VALVE WITH MANUAL RESET NC



## Product Description

Solenoid Valve for Gas aluminum normally closed with manual voltage - 230 Vac

- Version Threaded FF

**NOTE: Other voltages on request**

**VERSION AVAILABLE WITH P. MAX 6 bar**

*INCREASE OF 25% FROM NORMAL PRICE*



**PRESSIONE MAX 6 bar**  
P. MAX 6 bar



**PRESSIONE MAX 500 Mb**  
P. MAX 500 Mb

## Properties

Impiego	Gas non aggressivi delle 3 famiglie (gas secchi)
Temperatura di esercizio	-20°/+60°C
Tensione	12 V, 24 V, 110 V, 230 V
Potenza assorbita	8-9 VA
Grado di protezione /	IP 65
Classe	A

## Variants

Code	Mod. ø	Conf./Pack
50371	Ø 3/4" FF. alluminio	5
50372	Ø 1" FF. alluminio	5
50373	Ø 1 1/4" FF. alluminio	2
50374	Ø 1 1/2" FF. alluminio	2
50375	Ø 2" FF. alluminio	2



For further information on the product please contact our [technical department](#)

<http://www.tecnogas.net/en/products/elettrovalvola-per-gas-in-alluminio-a-riarmo-manuale-nc--3>