

FOR ALUMINUM GAS SOLENOID VALVE WITH MANUAL RESET NC



Product Description

Solenoid Valve for Gas aluminum normally closed with manual voltage - 230 Vac

- Flanged PN16

NOTE: Other voltages on request

VERSION AVAILABLE WITH P. MAX 6 bar
INCREASE OF 25% FROM NORMAL PRICE



PRESSIONE MAX 6 bar
P. MAX 6 bar



PRESSIONE MAX 500 Mb
P. MAX 500 Mb

Properties

Impiego	Gas non aggressivi delle 3 famiglie (gas secchi)
Temperatura di esercizio	-20°/+60°C
Tensione	12 V, 24 V, 110 V, 230 V
Potenza assorbita	18-20 VA
Grado di protezione /	IP 65
Classe	A

Variants

Code	Mod. ø	Conf./Pack
50376	Ø DN 65 alluminio	1
50377	Ø DN 80 alluminio	1
50378	Ø DN 100 alluminio	1
50379	Ø DN 125 alluminio	1
50380	Ø DN 150 alluminio	1

50381	Ø DN 200 alluminio	1
50382	Ø DN 300 alluminio (Prezzo su richiesta)	1

To view or download the price list click [Catalogs](#)
For further information on the product please contact our [technical department](#)

<http://www.tecnogas.net/en/products/elettrovalvola-per-gas-in-alluminio-a-riarmo-manuale-nc-4>