

UPRIGHT TANK

HIGH-
PERFORMANCE
HEAT EXCHANGER
UPRIGHT TANK

HRS 200

HRS 300

HRS 400

HRS 500

HRS 750


HRS 900



AE
Austria Email

HIGH-PERFORMANCE HEAT EXCHANGER UPRIGHT TANK - HRS 750, 900

HRS 750, 900



- Internal boiler enamelled according to DIN 4753 T3
- Operating pressure: max. 10 bar
- Operating temperature: max. 95 °C
- Straight-tube heat exchanger with very large heating surfaces
- With new, 100 mm ECO SKIN insulation
- Circulation: 5/4"
- Variable sensor position (sensor channel)
- High-quality dial thermometer attached
- With built-in impressed current anode
- 6/4" sleeve for SH screw-in heater for electrical backup heating (sealed)

ACCESSORIES:

- Mounted thermometer charge pump controller combination ATR
- Flange immersion heater, 240 mm
- 6/4" screw-in heater, "SH" series
- Impressed current anode (add-on kit)
- Finned tube heat exchanger
- For more information, please see our accessories brochure

Type	Dimension in mm								Diagonal height in mm	Pipe array heating surface in m ²	Pipe array capacity in l	Weight in kg	N _L number	ETF ¹⁾ in mm	ETE ²⁾ in mm
	H	H with insulation	ø D	A	B	C	E	F							
HRS 750	1882	2000	790	1265	1000	1165	1310	1580	1960	6,0	39,6	317	34	850	850
HRS 900	2228	2350	790	1445	1180	1345	1490	1920	2300	7,5	49,7	374	42	850	850

1) Installation depth of flange (for built-in heater of finned tube heat exchanger)

2) Installation depth of screw-in heater sleeve for SH heating

		Throughput performance in kW															
Supply temperature		70°C	70°C	70°C	70°C	80°C	80°C	80°C	80°C	70°C	70°C	70°C	70°C	80°C	80°C	80°C	80°C
Hot water temperature		45°C	45°C	45°C	45°C	45°C	45°C	45°C	45°C	60°C	60°C	60°C	60°C	60°C	60°C	60°C	60°C
Cold water temperature		10°C	10°C	10°C	10°C	10°C	10°C	10°C	10°C	10°C	10°C	10°C	10°C	10°C	10°C	10°C	10°C
Heating circuit flow rate		500l/h	1000l/h	2000l/h	3000l/h	500l/h	1000l/h	2000l/h	3000l/h	500l/h	1000l/h	2000l/h	3000l/h	500l/h	1000l/h	2000l/h	3000l/h
HRS 750	kW	28,5	46,8	71,3	87,4	35	59,1	92,1	114	22,6	34,4	49,7	59,4	29	48,4	72,1	87,4
	l/h	700	1149	1752	2147	860	1452	2262	2801	390	591	855	1021	500	832	1240	1503
HRS 900	kW	30,5	54,5	84,9	103,4	36,9	66,3	104,7	128,5	27	46,7	70,5	84,8	34,6	61,2	95,1	116,1
	l/h	765	1347	2097	2555	912	1639	2588	3174	468	811	1223	1471	601	1061	1650	2014

ECO DESIGN - LABELING

Type	Content in litres	Heat loss in EN 12897		Zapf Profile	Energy Efficiency Class
		in kWh/24h	in Watt		
HRS 200	200	1,67	69,6	XL	C
HRS 300	300	2,08	86,7	XXL	C
HRS 400	400	2,45	102,1	XXL	C
HRS 500	500	2,72	113,3	3XL	C
HRS 750	750	2,56	106,7	3XL	-
HRS 900	900	2,87	119,6	4XL	-



WE MANUFACTURE
IN AUSTRIA AND
DELIVER TO EUROPE

Head office and factory: Austria Email AG

A-8720 Knittelfeld, Austriastrasse 6
Phone (03512) 700-0, Fax (03512) 700-239
Internet: www.austria-email.at
E-mail: office@austria-email.at
Customer Service: Phone (03512) 700-297
E-mail: kundendienst@austria-email.at

Sales offices Germany:

Germany North/East
D-14770 Brandenburg, Beetzseeufer 3
Phone 0049/(0)3381 / 766-0
Fax 0049/(0)3381 / 766-244
E-mail: sgobi@austria-email.at

Germany South

D-92637 Weiden/Opf., Parksteiner Strasse 49
Phone 0049/(0)961 / 63 490-0
Fax 0049/(0)961 / 63 490-30
E-mail: ahirmer@austria-email.at

AE
Austria Email